

Φ5mm Power NTC Thermistor 47μF MF72-SCN5D-5 For Limiting Inrush Current

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Delivery Time:
- UL,REACH,RoHS,ISO MF72-SCN5D-5

5-8 work days

SOCAY

Shenzhen, Guangdong, China

- 2000PCS / 1000PCS
- Negotiable



Product Specification

- Description: NTC Thermistor • Footprint: Φ5mm • R25: 5Ω 1A • Imax: • Resistance Under Load: 353mΩ 6mW/ • δ: 20 Secs. • T: 47µF • C: • Storage Temperature -10 To +40 Range:
- Highlight:

5mm Power NTC Thermistor, Power NTC Thermistor 47µF, NTC 5D-5



More Images



Product Description

Φ5mm Power NTC Thermistor 47μF MF72-SCN5D-5 For Limiting Inrush Current

DATASHEET: MF72-SCN5D-5_v2105.1.pdf

Features:

RoHS & Halogen Free (HF) compliant Body size: φ5mm Radial lead resin coated High power rating Wide resistance range Cost effective Operating temperature range: -40~+200 Agency recognition: UL /cUL/RoHS

Part Number	Resistance at 25 ±20%	Max. Permissible Working Current	Resistance under Load (mΩ)	Dissipation Factor	Thermal Time Constant	Maximum permissible capacitance @240Vac
	R ₂₅ (Ω)	I _{max} (A)	(mΩ)	δ(mW/)	т(Sec.)	C(uF)
MF72-SCN5D-5	5	1	353	6	20	47

Structure and Dimensions (Unit: mm)



D max	T max	P max			L _{short} /L _{long}		Туре
6.0	4.0	3.0	5±0.5	-	7±1/20 ± 1	0.55	S
6.0	4.0	3.0	5±0.5	10±1	4±1/20 ± 1	0.55	K/V/D
Note: Length o	f Pin (L) can be	customized.		-			

Packing Specifiction				
Part Number	Type of L	Quantity (pcs/bag)		
	Lshort	2000		
MF72-SCN5D-5	Liong	1000		

ltem	Test conditions / Methods	Test Result
Tensile Strength of Terminals	Fasten body with a Load Applied to each lead 3.0Kg for 1sec.	No break out and damage
Bending Strength of Terminals	Fixed body hand 1.0kg on one terminal bend 90 then back again oppsite.	No break out and damage
Solder Ability	When the Lead wire was dipped into bath 0f 235 ± 5 for 3 seconds after immersion in 25% rosin flux the solder ability ratio of lead wire surface should more than 95%.	More than 95% solder ability

Temp. Cycle Test	(-40 ×→+25 ×3min) × 5Cycles (-85 ×→+25 ×3min) × 5Cycles	ΔR/R ≤ ±20 %
Humidity Test	45 95%RH×1000 hours	ΔR/R ≤ ±20 %
Load Life	6 AMP×1000 hours	ΔR/R ≤ ±20 %
Insulation Test	DC 700V	R≥500M

About NTC

An NTC thermistor is a resistor whose resistance changes with temperature. NTC stands for "Negative Temperature Coefficient", which means negative temperature coefficient. This means that as the temperature increases, the resistance value of the NTC thermistor will decrease.

NTC thermistors are commonly used to measure and control temperature. For example, they can be used in temperature sensors such as those that measure battery temperature, temperature controllers that control home heating systems, car engine control systems, and more. When the NTC thermistor is placed where the temperature needs to be measured or controlled, it will reflect the temperature change and change the resistance value accordingly. The change in temperature is calculated by measuring the change in resistance value.

In addition, NTC thermistors are also widely used for temperature compensation in circuits. When electronic components are working, their electrical properties will change due to temperature changes, and NTC thermistors can be used to compensate for this change. For example, using NTC thermistors in circuits can stabilize the circuit's working performance to a certain extent.

NTC thermistors are widely used in industry, automobiles, homes and other fields, and are commonly used sensors and electronic components.

About SOCAY

we are manufacturer and supplier of NTC ,DIODES ect passive components more than 20 years from China .if you have any request please contact us freely .

	SOCAY [®] Shenzhen Socay Electronics Co., Ltd.			
٢	+8618126201429	sylvia@socay.com	© socaydiode.com	
4/F, Block C, HeHe	ngXing Science & Tech Gua	nology Park, 19 MinQing Ro angDong Province, China	oad, LongHua District, Shenzhen City,	